





REAR VIEW

CAB CAB & CHASSIS MODEL: 2023 SPARTAN FC-94 MFD 10" RR ENGINE: CUMMINS L9 380HP @ 2200 RPM HORSEPOWER 1150 LB/FT. @ 1200 RPM, GOV 2200RPM ENGINE TORQUE: TRANSMISSION: ALLISON 3000 EVP FRONT AXLE RATING 18,000 LBS REAR AXLE RATING: 24,000 LBS.

BODY MATERIAL

.188 5052 H32 MARINE GRADE ALUM. .188 & .125 3003 H22 ALUM. CHECKER PLATE ALUMINUM EXTRUSIONS (SUBFRAME)

<u>PUMP</u>

HALE QFLOW (5000 LPM)

FOAM SYSTEM

N/A

WATER TANK

1000 USG POLYTANK

30 USG FOAM INTEGRATED CELL

COMPARTMENT DIMENSIONS

	INTERIOR (APPROX.)			DOOR OPENING (APPROX.) W/ DOOR INSTALLED	
	W	Н	D	W	Н
L1	48.5	77	27	45	68
L2	68	42	27	66	33
L3	48.5	77	27	45	68
R1	48.5	77	14.5/27	45	68
R2	68	42	14.5/27	66	33
R3	48.5	77	14.5/27	45	68
В1	44	47.5	31.5	38	37
INT	FRIOR C	LIBIC	FFFT.	W X H X D.	/ 1728

IMPORTANT NOTES

LADDER STORAGE: -DUO SAFETY LADDERS

ONE(1)900A 24' 2 SECTION

ONE(1)375A 14' ROOF
ONE(1)585A 10' ATTIC FOLDING
TWO(2) PIKE POLES – 12' MAX. LENGTH

SUCTION STORAGE:

TWO(2) 6"X10' TOP REAR LS,RS.

PC	1	PRELIMINARY DRAWING	11/02/2022
INIT.	REV.	DESCRIPTION	DATE
	CTO	MED. STOOK BUILDED FOOA	

DWG. #:

2202

DEPENDABLE EMERGENCY VEHICLES

THIS DRAWING IS A CLOSE APPROXIMATION OF YOUR FIRE APPARATUS IN ALL CASES WHERE THE DRAWING AND THE WRITTEN SPECIFICATION DIFFER, THE SPECIFICATION SHALL PREVAIL. PLEASE WORK WITH YOUR DEALER TO ASSURE THAT THE WRITTEN SPECIFICATION REPRESENTS WHAT YOU WANT IN YOUR FINISHED PRODUCT

APPROVED BY CUSTOMER:

SALES CONCEPTUAL DRAWING ONLY ALL DIMENSIONS ARE IN INCHES

ALL DIMENSIONS ARE SUBJECT TO CHANGE DUE TO MANUFACTURING PROCESSES

UNLESS OTHERWISE NOTED. TOLERANCES ARE: 3RD ANGLE PROJECTION THIS DRAWING IS THE CONFIDENTIAL PROPERTY OF DEPENDABLE EMERGENCY VEHICLES

DRAWN BY: APPROVED BY. PAGE:

SCALE:

STOCK PUMPER FC94 DESCRIPTION: DEV STOCK 2202 PUMPER FC94 SPEC. #.

11/02/22

DATE: