



CAB	
CAB & CHASSIS MODEL:	2024 FREIGHTLINER M106+ 2DR.
ENGINE:	DD8 7.7L
HORSEPOWER:	375 HP @ 2200 RPM GOV 2600 RPM
ENGINE TORQUE:	1050 LB/FT. @ 1200 RPM
TRANSMISSION:	ALLISON 3000 EVS
GVWR:	62,000 LBS.
FRONT AXLE RATING:	16,000 LBS.
REAR AXLE RATING:	46,000 LBS.

BODY MATERIAL	
POLY BODY	
.188 5052 H32 MARINE GRADE ALUM.	
.188 & .125 3003 H22 ALUM. CHECKER PLATE	

PUMP	
HALE DSD (5000 LPM)	

FOAM SYSTEM	
-	

WATER TANK	
3000 USG	
30 FOAM TANK	

GENERATOR	
N/A	

COMPARTMENT DIMENSIONS					
	INTERIOR (APPROX.)			DOOR OPENING (APPROX.) W/ DOOR INSTALLED	
	W	H	D	W	H
L1/R1	56.5	37.5	24.5	54.5	27.5
L2/R2	35.5	37.5	24.5	33.5	27.5

INTERIOR CUBIC FEET: W X H X D / 1728

- IMPORTANT NOTES**
- LADDER STORAGE:
 - 24' 2-SECT DUO SAFETY LADDER
 - 14' ROOF LADDER
 - 10' ATTIC FOLDING LADDER

PC	2	BACK WALL SMALL LIGHTS REMOVED/ HB PRECONNECT ADDED TO FRONT WALL ON RS.	09/21/2023
PC	1	PRELIMINARY DRAWING	04/04/2023
INIT. REV.		DESCRIPTION	DATE



THIS DRAWING IS A CLOSE APPROXIMATION OF YOUR FIRE APPARATUS IN ALL CASES WHERE THE DRAWING AND THE WRITTEN SPECIFICATION DIFFER, THE SPECIFICATION SHALL PREVAIL. PLEASE WORK WITH YOUR DEALER TO ASSURE THAT THE WRITTEN SPECIFICATION REPRESENTS WHAT YOU WANT IN YOUR FINISHED PRODUCT

APPROVED BY CUSTOMER: _____

SALES CONCEPTUAL DRAWING ONLY

ALL DIMENSIONS ARE SUBJECT TO CHANGE DUE TO MANUFACTURING PROCESSES

UNLESS OTHERWISE NOTED:
TOLERANCES ARE:
3RD ANGLE PROJECTION
THIS DRAWING IS THE CONFIDENTIAL PROPERTY OF DEPENDABLE EMERGENCY VEHICLES

DRAWN BY: PC
APPROVED BY:
PAGE:
SCALE:
CUSTOMER: DEV 3000 USG POLYBODY INTERGRATOR
DESCRIPTION: TANKER
SPEC. #: 2207
DATE: 04/04/2023
DWG. #: 2207